

VS20 Machine Vision Smart Sensor

Easily integrate machine vision into your network



From the factory floor to the control room, manufacturers are under intense pressure to meet increasing business demands. Every day, production lines strive to achieve consistent product quality and throughput quotas. Success requires a reliable and dependable process at every stage of production—a process that increases automation, reduces defects and validates assembly and tracking information.

Address it all with the Zebra VS20 Machine Vision Smart Sensor. With multiple connectivity options, the compact VS20 easily integrates into your PLC or Host network to perform essential quality inspections, providing a new level of intelligence and automation to improve product quality and meet production goals. The result? Leaner operations. Fewer product defects. Lower manufacturing costs. And more satisfied customers.



The VS20 brings a new level of simplicity to your machine vision solutions. It all starts with Zebra Aurora—a powerful and intuitive software platform that makes it exceptionally easy to set up, deploy and run Zebra's entire portfolio of Machine Vision Smart Cameras and Fixed Industrial Scanners. Zebra-exclusive features such as ImagePerfect reduce steps, training and management time and cost, as well as the need for external peripherals. And since you can add advanced tools at any time with a simple software license upgrade, the device you buy today can support new needs tomorrow.

Take your success to the next level with extraordinary visibility into your operational processes—with the VS20, only from Zebra.

Zebra Aurora[™] Software

A Single Unified Platform Across Zebra's Fixed Industrial Scanner and Machine Vision Portfolio

Zebra Aurora brings a new level of simplicity to controlling enterprise-wide manufacturing and logistics automation solutions. This powerful interface makes it easy to set up, deploy and run all of Zebra's Fixed Industrial Scanners and Machine Vision Smart Cameras, while eliminating the need for different tools.

For Experts and Beginners

Experienced and first-time users can easily navigate the highly intuitive modern interface, reducing training and deployment time. Experienced users will appreciate easy access to all functions and streamlined processes, while first-time users are guided through all the steps in the proper order. And if users need a little help, Learn-As-You-Go offers built-in tutorials, walkthroughs and videos on all aspects of the software and its comprehensive management toolset.

Easy to Set Up

Automatic Setup With Auto-Tune

Just Auto-Tune and run for consistent, reliable inspections—right out of the box. With the press of one button, Auto-Tune dials in the perfect image for faster and more accurate set up.

IoT Ready With Zebra Savanna™

The IoT-ready VS20 can send images to Zebra's subscription-based cloud service, Zebra Savannaor any other cloud service—allowing you to meet industry regulations or store images for further analysis, all without the need to purchase and manage servers.

Power it All Over Ethernet

Reduce setup complexity and cost with support for Power-over-Ethernet (PoE). This standard feature powers the VS20 and attached accessories right over the network, eliminating the cost of power drops and power supplies. Don't have a PoE infrastructure? No problem. You can also power the VS20 with a standard 24V DC power supply.

Create Tools Faster With QuickDraw

Simply draw right on an image to create a tool in fewer steps than most competitive systems require.

Locate the Right Part Successfully—Every Time

Zebra takes a new approach to the creation of two key error-proofing tools—Object Locate and Pattern Matching. Zebra's optimized algorithms and carefully crafted default settings enable users to dependably create successful tools with fewer clicks, less trial and error, and less deployment time and effort.

Easy to Deploy

Programmable Input/Output (I/O) Ports

Get the ultimate in I/O flexibility. Four digital I/O ports can be individually controlled to expand application functionality and improve errorproofing. Support additional peripherals, activate lights, or trigger an action to more fully automate vour processes.

Ultra-Rugged and Ready for Industrial Spaces

Rely on dependable operation in the most demanding environments with an ultra-rugged design. The aluminum housing is chemical and oil resistant and IP65-sealed.

Operator Feedback/Status Indicators

With four built-in camera status LEDs—Power. Decode, Online/Run and Ethernet Status—workers can see at a glance if a decode was successful or unsuccessful, protecting product quality and traceability—and whether cameras are operational or in need of attention. In addition, a beeper with adjustable volume provides an audible cue of a successful decode, so workers can keep their eyes on the job-instead of the device.

Added Flexibility With the Zebra Aurora **HMI** dashboard

Give workers actionable intelligence right where they need it—at their station. Operators can see and interact with the Zebra Aurora Human Machine Interface (HMI) dashboard via any web browser. The need to install a PC at every workstation is eliminated, reducing hardware requirements and installation costs.

Simple, Easy And Fast Integration With Your **Network Infrastructure**

Built-in Ethernet/IP, PROFINET and other network protocols enable painless integration with any common PLC or host system. Network architecture is simplified and deployment time and cost are reduced.

Key Differentiators

The VS20 is loaded with class-leading features, including:

ImagePerfect

Eliminate bypassed systems and false rejects with perfect images

In one trigger event, capture up to three different images, each with its own unique setting for focus, exposure gain, illumination control and more.

Golden Image Compare

Rapid troubleshooting for failed image capture

Compare any image to a golden 'perfect' image created at setup to immediately locate the source of the image degradation—such as a dirty lens, lighting issue or misalignment of the camera.

Software Upgradeable

Add what you need, whenever you need it

Add support for new barcode symbologies, faster barcode capture and all the machine vision tools you need through simple software licensing.

Power it all over Ethernet

Power the VS20 right over your Ethernet cable—no more costly power drops and no more power supplies to purchase and manage.

Easy to Run

Eliminate Bypassed Inspections and False Rejects With ImagePerfect

Uneven lighting and the need to read images at various distances can require additional cameras, external lights or complex custom code—additions that can substantially increase the total cost of ownership. Address it all with a groundbreaking new feature—ImagePerfect. This Zebra-exclusive feature captures up to three different images of a single item, each with its own unique setting for focus, exposure, gain, illumination control and more. The result? High quality images that enable high read rates. A significant reduction in solution complexity. And a lower total cost of ownership.

Get the Features You Need Today and Add the Features You Need Tomorrow

The modular architecture lets you select the Machine Vision (MV) toolset you need now, and add new functionality any time in the future. Just purchase licenses to upgrade to more advanced MV tools, allowing you to meet tomorrow's needs with the products you have today.

First-Time Every-Time Barcode Capture

Need to capture barcodes? Superior optics and Zebra's exclusive PRZM Intelligent Imaging technology work together to deliver the reliable data capture you need to keep your operations running at peak capacity. The optical system enables the simultaneous capture of multiple

barcodes, extends read ranges and focal distances and allows a larger field of view to capture more information with less equipment. And PRZM Intelligent Imaging delivers first-time capture of virtually any 1D, 2D and DPM barcode on any surface, in practically any condition.

Rapid Troubleshooting With Golden Image Compare

If any image capture or barcode reads fail, this Zebraonly tool allows you to quickly identify and resolve the issue by comparing any image to a golden 'perfect' image created at setup. Minimize downtime by immediately diagnosing and rapidly correcting the source of any degradation—from a dirty lens or a lighting problem to misalignment of the camera.

Complete Support Service—Everything's Covered

Get the constant peak performance and device uptime today's businesses demand with Zebra OneCare™ Essential and Select Support Services. Unexpected disruptions and unbudgeted repair expenses are eliminated. Everything is covered—including normal wear and tear and accidental damage. You can customize your support plan with numerous options to get the service level your business needs, including next-day delivery of a replacement device, on-site support, cloud-based visibility into your contracts, repair data, tech support cases—and more.

Introducing the Zebra Fixed Industrial Scanner and Machine Vision Portfolio



FS10



FS20/VS20



FS40/VS40



FS70/VS70

Specifications

Dimensions	1.1 in. H x 3.7 D in. x 2.1 in. W 28.3 mm H x 94.2 mm D 54.6 mm W	
Weight	7.76 oz./195 g	
Power	External power supply: 10-30 VDC, 313 mA max @ 24 VDC (7.5 W) PoE supply: Class 2	
Configurable IO	Two opto-isolated inputs: IN 1,2 Two opto-isolated outputs: OUT 1,2	
Color and Material	Industrial green aluminum housing	
Interface Ports	One M12 X-Coded 1000/100/10 Mbps Ethernet One M12 12-pin Power/GPIO/RS-232	
Communication Protocols	Ethernet/IP, PROFINET, Modbus TCP, TCP/IP, RS-232	
User Indicators	Decode Status LEDs, Power LED, Online/Run LED, Ethernet Status LED; Beeper	
Performance Characte	eristics	
Image Sensor	1/4 inch CMOS, global shutter 1280 x 800, 3.0 um square pixels Monochrome	
Acquisition Rate	Up to 60 frames/second	
Aimer	Amber LED; circular pattern	
Illumination	Two 660nm Red LEDs or two 2700K White LEDs	
Imager Field of View	6.0mm Liquid Lens: 35° H x 26° V Nominal	
User Environment		
Operating Temp.	32° F to 113° F/0° C to 45° C (10-30VDC external power supply, duty cycle-dependent) 32° F to 113° F/0° C to 40° C (PoE, duty cycle-dependent)	
Storage Temp.	-40° F to 158° F/-40° C to 70° C	
Environmental Sealing	IP65 and IP67	
Humidity	5% to 90% RH, non-condensing	
Shock Resistance	EN 60068-2-27, 30 g; 11 ms; 3 shocks on each axis	
Vibration Resistance	EN 60068-2-6, 14 mm @ 2 to 10 Hz, 1.5 mm at 13 to 55 Hz; 2 g at 70 to 500 Hz; 2 hours on each axis	
Supported Symbologic	es²	
1D	Codabar, Code 39, Code 93, Code 128, I 2 of 5, MSI Plessey, UPC/EAN	
2D	Aztec, Data Matrix, DotCode, MaxiCode, PDF417, Micro PDF417, QR Code, Micro QR	
OCR	Deep Learning-based OCR via an add-on license'. Supports Latin Letters (A-Z, a-z, digits	

Software	
Management	Zebra Aurora
Decoder Packages	Included in Standard and Advanced Machine Vision toolsets: 1D/2D Standard (5 FPS); 1D/2D Fast (60 FPS); 1D/2D DPM Full (60 FPS)
Machine Vision (MV) Toolsets	Sensor, Standard, Advanced (MV toolsets vary by SKU; upgrades available via a software license)
Regulatory	
Environmental	EN 50581:2012; EN IE C 63000:2018
Electrical Safety	IEC 62368-1 (Ed.2); EN 62368-1:2014/A11:2017
LED Safety	IEC 62471:2006 (Ed.1); EN 62471:2008
EMI/EMS	EN 55032:2015/A11:2020 (Class B) EN 55035:2017 EN 61000-3-2:2014 (Class A) EN 61000-3-3:2013 47 CFR Part 15, Subpart B, Class B ICES-003, Issue 7, Class B
EU Declaration of Conformity	2014/30/EU; 2014/35/EU; 2011/65/EU. For more information visit: www.zebra.com/doc
Accessories	
Brackets, cables, power	supplies
Warranty	
warranted against defect	ebra's hardware warranty statement, the VS20 is is in workmanship and materials for a period of Two (2) ipment. Complete Zebra hardware product warranty pm/warranty
Recommended Ser	vices
Zebra OneCare Select™;	Zebra OneCare Essential™

Specifications

Decode Ranges (Typical Working Ranges)³

VS20-SR—35° FOV Lens		
Symbology/Resolution	Near	
5 mil Code 128	2 in./5.08 cm	10
10 mil Code 128	2 in./5.08 cm	15

, ,,		
5 mil Code 128	2 in./5.08 cm	10 in./25.4 cm
10 mil Code 128	2 in./5.08 cm	15 in./38.1 cm
15 mil Code 128	2 in./5.08 cm	20 in./50.8 cm
20 mil Code 128	2 in./5.08 cm	24 in./61.0 cm
5 mil DataMatrix	2.5 in./6.35 cm	7.7 in./19.56 cm
10 mil DataMatrix	2 in./5.08 cm	15 in./38.1 cm
15 mil DataMatrix	2 in./5.08 cm	20 in./50.8 cm

Far

Footnotes

- Some features available in a future release. Contact your Zebra Partner or sales representative for more information.
- 2. Refer to Product Reference Guide for complete list of symbologies.
- 3. Printing resolution, contrast, illumination source, and ambient light dependent.

Specifications subject to change without notice.

Mach	nina	Vision	(MV)	Tools

Tool	Description	Sensor	Standard	Advanced
Object Locate	Find high contrast features	•	•	•
Pixel Counter	Count pixels with a set/given grey level in a specific area	•	•	•
Brightness	Provide the average brightness for an area	•	•	•
Contrast	Provide the average contrast for an area	•	•	•
Edge Tool	Find edges for fixturing and presence/absence	•	•	•
Distance Tool	Measure the distance between two existing tool results	•	•	•
Advanced Pattern	Find challenging features		•	•
Blob	Find, sort and count areas of joined pixels with a similar grey level		•	•
Optical Character Verification (OCV)	Inspects the quality of text or logos		•	•
Find Circle	Find and measure circles		•	•
Caliper Tool	Find and measure the distance between two edges		•	•
Filters	Enhance image quality for more robust inspection		•	•
1D/2D/DPM	Read 1D, 2D and DPM barcodes		•	•
Deep Learning OCR	Deep Learning-based OCR			•

